



DB100-STL / DB125-STL

DOLPHIN ELECTRONIC INFRARED TAP

- > **WRAS Approved product**
- > Touch Free Tap – for ultimate hygiene – prevents cross contamination
- > Quality polished or brushed chrome plated brass finishes available from stock – other finishes available to special order
- > Water Supply: 3/8 inch single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- > Flow rate - 3.8 litres/minute with our standard fitted flow regulator at any pressure between 0 and 6 bar (other flow rates such as 1.89 and 1.33 LPM available to special order - please enquire)
- > Flow time once user's hands are removed from the tap – 1 second (adjustable by using remote control DB51)
- > Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WAT 1 credits
- > Power cable length - 3 meters
- > Interchangeable STD M22/24 Neoperl Aerator insert
- > Tap settings can be adjusted manually or by using remote control (DB51)
- > Mandatory Hygiene Flush feature can be specified to combat Legionella – please specify a time of ordering
- > 2 year manufacturer's warranty
- > Max water temperature 70°C
- > Very low energy usage
- > We recommend our Dolphin Blue DB61 TMV3 be used in conjunction with this Dolphin Blue tap
- > Listed on the Government's Water Technology List (WTL) as part of the Enhanced Capital Allowance (ECA) scheme. The ECA allows a business to offset the cost of purchasing eligible plant and machinery against its taxable profits
- > Power connections: soap dispenser: male / power source: female

HEIGHT	172 MM
DIAMETER	50 MM
PROJECTION	91 MM

PRODUCT CODES

BATTERY POWERED

- > Polished Chrome **DB100C-STL**
- > Brushed/Satin Chrome **DB100S-STL-2**

TRANSFORMER POWERED

- > Polished Chrome **DB125C-STL**
- > Brushed/Satin Chrome **DB125S-STL-2**