



DB250 / DB275

## DOLPHIN ELECTRONIC INFRARED TAP WITH TEMPERATURE ADJUSTMENT LEVER

- > WRAS Approved product
- > Touch Free Tap – for ultimate hygiene – prevents cross contamination
- > Quality polished or brushed chrome plated brass finishes available from stock – other finishes available to special order
- > Water Supply: hot and cold supply featuring temperature adjustment lever
- > Flow rate – 3.8 litres/minute with our standard fitted flow regulator at any pressure between 0 and 6 bar (other flow rates such as 1.89 and 1.33 LPM available to special order – please enquire)
- > Flow time once user's hands are removed from the tap – 1 second (adjustable by using remove control DB51)
- > Interchangeable STD M22/24 Neoperl Aerator insert
- > Tap settings may be adjusted by using remote control (DB51)
- > Mandatory Hygiene Flush feature can be specified to combat Legionella
- > 2 year manufacturer's warranty
- > Power connections: tap: male / power source: female
- > Complies with SKA rating criteria
- > The two flexible connectors contain integral check (non-return) valves
- > We recommend our Dolphin Blue DB61 TMV3 be used in conjunction with this tap
- > Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAMWAT 1 credits.

<b>HEIGHT</b>	<b>142 MM</b>
<b>DIAMETER</b>	<b>50 MM</b>
<b>PROJECTION</b>	<b>60 MM</b>

- > Power Source: 9 Battery / Plug-in 9 Volt transformers
- > Power connections: tap: male / power source: female
- > 3/8" BSP water supply connector
- > Maximum water temperature 70°C
- > Operating pressure 0.5 - 8.0 bar (7 - 116 PSI)
- > Min-Max thickness: 2-27mm
- > Counter Hole: diameter 28-34mm
- > Minimum/maximum thickness: 2-27mm

### PRODUCT CODES

#### BATTERY POWERED

- > Polished Chrome **DB250C**
- > Brushed/Satin Chrome **DB250S-2**

#### TRANSFORMER POWERED

- > Polished Chrome **DB275C**
- > Brushed/Satin Chrome **DB275S-2**

TECHNICAL HELPLINE 01424 202224  
DOLPHINSOLUTIONS.CO.UK