



DB200 / DB225

DOLPHIN ELECTRONIC INFRARED TAP

- › Touch Free Tap – for ultimate hygiene – prevents cross contamination
- › Quality polished or brushed chrome plated brass finishes available
- › Water Supply: Single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- › Flow time once user's hands are removed from the tap - 1 second (adjustable by using remove control DB51)
- › Tap settings including optional hygiene flush can be adjusted by using remote control (DB51)
- › Mandatory Hygiene Flush feature can be specified to combat Legionella
- › 2 year manufacturer's warranty
- › WRAS Approved Product
- › Water supply: Single - cold or premixed
- › Mandatory Hygiene Flush is available - can be set to 12,24 or 48 Hour intervals - optional extra & must be specified when ordering
- › Flow rate – 3.8 litres/minute with our standard fitted flow regulator at any pressure between 0 and 6 bar (other flow rates available to special order – please enquire)
- › Complies with SKA rating criteria
- › Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WAT 1 credits.

| | |
|-------------------|---------------|
| HEIGHT | 142 MM |
| DIAMETER | 50 MM |
| PROJECTION | 60 MM |

- › Power Source: 9 Volt Battery / Plug-in 9 Volt transformer
- › Power connections: tap: male / power source: female
- › 3/8" BSP water supply connector
- › Maximum water temperature 70°C
- › Operating pressure 0.5 - 8.0 bar (7 - 116 PSI)
- › Min-Max thickness: 2-27mm
- › Counter Hole: diameter 28-34mm
- › Minimum/maximum thickness: 2-27mm

PRODUCT CODES

BATTERY POWERED

- › Same product in chrome plated brass **DB200C**
- › Same product in brushed nickel plated **DB200S**

TRANSFORMER POWERED

- › Same product in chrome plated brass **DB225C**
- › Same product in brushed nickel plated **DB225S**