



DB200 / DB225

DOLPHIN ELECTRONIC INFRARED TAP

- > WRAS Approved product
- > Touch Free Tap – for ultimate hygiene – prevents cross contamination
- > Quality polished or brushed chrome plated brass finishes available from stock – other finishes available to special order
- > Water Supply: Single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- > Flow time once user's hands are removed from the tap - 1 second (adjustable by using remove control DB51)
- > Tap settings including optional hygiene flush can be adjusted by using remote control (DB51)
- > Mandatory Hygiene Flush feature can be specified to combat Legionella
- > 2 year manufacturer's warranty
- > Water supply: Single – cold or premixed
- > Mandatory Hygiene Flush is available - can be set to 12,24 or 48 Hour intervals – optional extra & must be specified when ordering
- > Flow rate – 3.8 litres/minute with our standard fitted flow regulator at any pressure between 0 and 6 bar (other flow rates such as 1.89 and 1.33 LPM available to special order – please enquire)
- > Complies with SKA rating criteria
- > Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WAT 1 credits.
- > Listed on the Government's Water Technology List (WTL) as part of the Enhanced Capital Allowance (ECA) scheme. The ECA allows a business to offset the cost of purchasing eligible plant and machinery against its taxable profits

HEIGHT	142 MM
DIAMETER	50 MM
PROJECTION	60 MM

- > Power Source: 9 Volt Battery / Plug-in 9 Volt transformer
- > Power connections: tap: male / power source: female
- > 3/8" BSP water supply connector
- > Maximum water temperature 70°C
- > Operating pressure 0.5 - 8.0 bar (7 - 116 PSI)
- > Min-Max thickness: 2-27mm
- > Counter Hole: diameter 28-34mm
- > Minimum/maximum thickness: 2-27mm

PRODUCT CODES

BATTERY POWERED

- > Polished Chrome **DB200C**
- > Brushed / Satin Chrome **DB200S-2**

TRANSFORMER POWERED

- > Polished Chrome **DB225C**
- > Brushed / Satin Chrome **DB225S-2**

TECHNICAL HELPLINE 01424 202224
DOLPHINSOLUTIONS.CO.UK