



DBL400 / DBL425

## DOLPHIN PANEL MOUNTED ELECTRONIC INFRARED TAP - LONG SERIES

- › WRAS Approved product
- › Touch Free Tap – for ultimate hygiene – prevents cross contamination
- › Quality polished or brushed chrome plated brass finishes available
- › Water Supply: Single inlet – cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- › Flow rate – 3.8 litres/minute with our standard fitted flow regulator at any pressure between 0 and 6 bar (other flow rates such as 1.89 and 1.33 LPM available to special order – please enquire)
- › Flow time once user's hands are removed from the tap - 1 second (adjustable by using remove control DB51)
- › Interchangeable STD M22/24 Neoperl Aerator insert
- › Tap settings including optional hygiene flush can be adjusted by using remote control (DB51)
- › Mandatory Hygiene Flush feature can be specified to combat Legionella
- › 2 year manufacturer's warranty
- › Complies with SKA rating criteria
- › Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WAT 1 credits.
- › Listed on the Government's Water Technology List (WTL) as part of the Enhanced Capital Allowance (ECA) scheme. This allows businesses purchasing these product to benefit from 100% first year capital allowances on this expenditure.

**DIAMETER** 50 MM  
**PROJECTION** 220 MM

- › Power Source: 9 Volt Battery (with low battery warning)
- › Power Connections: tap female, power source male
- › Maximum water temperature 70°C
- › Operating pressure 0.5 - 8.0 bar (7 - 116 PSI)

### PRODUCT CODES

#### BATTERY POWERED

- › Polished Chrome Plate [DBL400C](#)
- › Brushed (Satin) Chrome Plate [DBL400S-2](#)

#### TRANSFORMER POWERED

- › Polished Chrome Plate [DBL425C](#)
- › Brushed (Satin) Chrome Plate [DBL425S-2](#)