



DBI50 / DBI75

DOLPHIN INFRARED TAP WITH TEMPERATURE ADJUSTMENT

- › Touch Free Tap – for ultimate hygiene – prevents cross contamination
- › Quality polished chrome plated brass finish stocked – other finishes available to special order
- › Water Supply: hot and cold supply with temperature adjustment lever. 3/8" BSP water supply connector
- › Flow rate – 3.5 litres/minute with our standard fitted flow regulator at any pressure between 0.5 and 8 bar (other flow rates such as 1.89 and 1.33 LPM available to special order – please enquire)
- › Power Source: Plug-in 9 Volt transformers or 9 Volt Battery (with low battery warning). Power connections: tap: male / power source: female
- › Counter Hole: diameter 28-34mm - Minimum/maximum thickness: 2-27mm
- › Flow time once user's hands are removed from the tap - 1 second (adjustable by using remote control DB51)
- › Interchangeable STD M22/24 Neoperl Aerator insert
- › Hygiene flush feature runs the tap for 25 seconds, 24 hours after the last use of the tap. This flush time or 24 hours interval cannot be changed and is not based on real time, the feature can only be switched on or off using a compatible remote control(DB51). Taps are supplied with this feature switched on
- › 2 year manufacturer's warranty
- › WRAS approved and complies with SKA rating criteria
- › The two flexible connectors contain integral check (non-return) valves
- › We recommend our Dolphin Blue AL0220 TMV3 be used in conjunction with this tap
- › Fully BREEAM compliant and contributes to up to five BREEAM WAT1 credits.
- › Listed on the Government's Water Technology List (WTL) as part of the Enhanced Capital Allowance (ECA) scheme. The ECA allows a business to offset the cost of purchasing eligible plant and machinery against its taxable profits

HEIGHT	172MM
DIAMETER	50MM
PROJECTION	135MM

PRODUCT CODES

DBI50C - Battery powered, polished finish

DBI75C - Transformer powered, polished finish



SKArating

