



09.3010

## DOLPHIN PAPER TOWEL AND WASTE BIN

### SPECIFICATION

Recess mounted modular paper towel dispenser and waste paper bin. Model number 09.3010 with flush mounted locks, vertically brushed satin finish stainless steel doors, chutes and stainless steel back boxes and bin. Manufactured by Dolphin Solutions Ltd.

N.B. For surface mounted version order 09.3410

WIDTH	375 MM
HEIGHT	1129.5 MM
PROJECTION	16 MM

## MATERIAL

- › Doors: 1.2mm satin finish stainless steel grade 1.4301 (304) to BS EN 10088-1
- › Chutes: 0.7mm satin finish stainless steel grade 1.4301 (304) to BS EN 10088-1
- › Bin: 0.7mm stainless steel grade 1.4301 (304) to BS EN 10088-1
- › Back boxes: 0.9mm stainless steel grade 1.4301 (304) to BS EN 10088-1

Approximate unit weight: 15kg

## CAPACITY

Paper Towels:	'C' Fold	Interleave
Length mm (min-max)	225-250	215-250
Width mm (min-max)	90-105	80-105
Quantity	200	300

### Waste Bin Capacity

- › Standard: 10 litres

## OPERATION

- › Paper towel dispenser holds and dispenses 200 'C' fold or 300 interleave paper towels. Flush mounted lock secures hinged door panel, which opens for refilling.
- › **Emptying of bin:** The bin can be accessed opening door with key supplied.
- › Open door; slide bin forward and remove from guide rails, fit suitable bin liner. Push bin back over slide rails into back box void and shut door.

## INSTALLATION

- › Recommended wall opening of 360w x 1112h x 112d
- › Recommended mounting height from underside of unit to FFL 315mm (Male Toilet).
- › Open doors with key provided
- › Position the unit into the prepared wall recess allowing a 6mm clearance all round for packing and adjustment
- › Fit temporary screws into the rectangular slots on the side walls (Do not over tighten, to allow for horizontal adjustment)
- › Fix casing to studwork using suitable screws (Fixing holes Ø6.5mm) and remove temporary screws from slots
- › Lock front covers

## CARE AND MAINTENANCE

- › Clean with soap and warm water; dry with a clean soft cloth.
- › To maintain finish use any industrial steel cleaner; polishing along the material grain with a clean soft cloth.
- › Dolphin recommends "Steel Clean" cleaning agent, obtainable from: Vitopan (Tel: 01 204 863000)
- › Never Use Corrosives - such as bleach or other cleaning products containing hypochlorite;
- › Any form of acid solution or industrial cleaning solution; Bathroom cleaning products, developer liquids, concentrated disinfectants, strong alkalis or caustic soda;
- › Never Use Abrasives - such as wire wool; scouring pads;
- › Caution - Never use dirty or grit contaminated cleaning sponges or cloths

## WARRANTY

This product is covered by a 12-month warranty from the date of purchase to be free from defects if installed and maintained in accordance with these instructions. Dolphin Solutions will replace or repair (as appropriate) free of charge any product with a proven manufacturing defect if reported within the warranty period.

Dolphin Solutions Ltd reserves the right to amend the design or dimensions without formal notice.