



DBI400 / DBI425

## DOLPHIN PANEL MOUNTED INFRARED TAP

- > WRAS Approved product
- > Touch Free Tap – for ultimate hygiene – prevents cross contamination
- > Quality polished or brushed chrome plated brass finishes available from stock – other finishes available to special order
- > Water Supply: Single inlet – cold or premixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- > Flow rate – 3.5 litres/minute with our standard fitted flow regulator at any pressure between 0 and 6 bar (other
- > flow rates such as 1.75 and 1.25 LPM available to special order – please enquire)
- > Flow time once user's hands are removed from the tap – 1 second (adjustable by using remote control DB51)
- > Interchangeable TT M16/18 Neoperl Aerator insert
- > Auto adjusting sensor range 50-170 mm
- > 2 year manufacturer's warranty
- > To combat Legionella, hygiene flush feature runs the tap for 25 seconds, 24 hours after the last use of the tap. This flush time or 24 hours interval cannot be changed and is not based on real time, the feature can only be switched on or off using a compatible remote control (DB51). Taps are supplied with this feature switched on
- > Maximum water temperature 70°C
- > Operating pressure 0.5–8.0 bar (7–116 PSI)
- > To special order we can supply a threaded tail extension kit
- > Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WAT 1 credits.
- > Listed on the Government's Water Technology List (WTL) as part of the Enhanced Capital Allowance (ECA) scheme. This allows businesses purchasing these product to benefit from 100% first year capital allowances on this expenditure.
- > Base diameter is 23 mm OD.
- > 24mm diameter hole in glass splashback recommended.

<b>DIAMETER</b>	<b>28MM</b>
<b>PROJECTION</b>	<b>220MM</b>

### PRODUCT CODES

- DBI400C** - Polished Chrome Battery Powered
- DBI400S-2** - Satin Chrome Battery Powered
- DBI400-316** - Satin Stainless Steel Battery Powered
- DBI425C** - Polished Chrome Transformer Powered
- DBI425S-2** - Satin Chrome Transformer Powered
- DBI425-316** - Satin Stainless Steel Transformer Powered

