



**DB1650**

## DOLPHIN MONOBLOC MIXER TAP

- > WRAS Approved product
- > Superior quality for prestigious washrooms
- > Solid stainless steel in a brushed finish
- > Single lever basin tap
- > Interchangeable STD M22/24 Neoperl Aerator insert
- > 2 inlet (hot and cold) water supply
- > Counter hole Ø 34-40mm
- > Maximum counter thickness 43mm
- > Inlet via 2 flexible connectors with 1/2" BSP connection
- > Flow rate – 3.5 litres/minute with our standard fitted flow regulator at any pressure between 0.5 and 6 bar (other flow rates such as 1.89 and 1.33 LPM available to special order – please enquire)
- > We recommend our Dolphin Blue-AL0220 TMV3 be used in conjunction with this Dolphin Blue tap
- > Exceeds the BREEAM requirements for taps for a maximum flow rate of less than 6 litres per minute (LPM) at a water pressure for 0.3 mega pascals (MPa)
- > Max water temperature 90°C
- > Max operating pressure 6.0 bar

<b>HEIGHT</b>	<b>157MM</b>
<b>DIAMETER</b>	<b>45MM</b>
<b>ROSE DIAMETER</b>	<b>55MM</b>
<b>PROJECTION</b>	<b>118MM</b>

