



DS101

DOLPHIN THRU PANEL MOUNTED INFRARED TAP

- › Dolphin Thru Panel Mounted InForm Tap
- › Manufactured from high-quality, highly durable 1.4401 (316) Marine grade stainless steel.
- › Self-monitoring analysis and recording technology (smart) allows the facilities Manager to connect point to point via the Dolphin InForm App when used with the optional Bluetooth Adaptor (Sold separately – Order product code 25148)
- › 90° spout
- › Infrared Touch Free Tap – for ultimate hygiene – prevents cross contamination – sensor mounted in end of spout
- › Designed to be mounted through an IPS panel.
- › Flow rate – nominal 3.5 litres/minute (other flow rates such as 1.75 and 1.25 LPM available to special order – please enquire)
- › Operating pressure: 0.5 bar minimum to 8.0 bar maximum
- › Water supply: single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- › Maximum operating water temperature - 65°C
- › Power supply
- › Nominal current: Less than 1mA (Less than 25mA with Bluetooth)
- › Nominal power: Less than 1W
- › Security time can be adjusted via the App – default 20 seconds (60 seconds max)
- › IP68 connector
- › Available in Satin or Polished, stainless steel, PVD finishes, or powder coated to any RAL colour of your choice
- › Powered by a hard wired transformer, plug transformer, or battery pack
- › Available with a laminar flow option instead of standard aerator
- › Comes as standard with 24 hour line purge/hygiene flush feature, with alterable timings

PROJECTION 130/180/230/280MM
DIAMETER 28MM

PRODUCT CODES

DS101.xxx.xx xxx - Main tap code e.g. DS112
xxxxx.230.xx xxx - Tap length, e.g. 230mm
xxxxx.xxx.01 xxx - Tap finish, e.g. 01 = satin
xxxxx.xxx.xx BATT - Power type, e.g. BATT = battery pack



TECHNICAL HELPLINE 01424 202224
DOLPHINSOLUTIONS.CO.UK