



DS211
DOLPHIN INFORM SLIMLINE BASIN TAP

- > Dolphin Up and Over Thru Counter Mounted Inform Tap
- > Manufactured from high-quality, highly durable 1.4401 (316) Marine grade stainless steel
- > Self-monitoring analysis and recording technology (smart) allows the Facilities Manager to connect point to point via the Dolphin Inform App when used with the optional Bluetooth Adaptor (Sold separately – Order product code 25148)
- > 90° spout
- > Infrared Touch Free Tap – for ultimate hygiene – prevents cross contamination – sensor mounted in end of spout
- > Standard Flow rate – 3.0 litres/minute with the flow regulator (fitted adjacent to solenoid) at any pressure between 0.5 and 6.0 bar; but typically at 3 bar
- > Other flow rates available – 1.0 litre/minute, 2.0 litres/minute and 4.0 litres/minute – please specify clearly if one of these alternative flowrates are required.
- > Operating pressure: 0.5 bar minimum to 8.0 bar maximum
- > Water supply: single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- > Maximum operating water temperature - 60°C
- > Nominal current: Less than 1mA (Less than 25mA with Bluetooth)
- > Nominal power: Less than 1W
- > Security time can be adjusted via the App – default 20 seconds (60 seconds max)
- > IP68 connector
- > Power Source: Plug-in 9 Volt transformers

DIAMETER **22 MM**
PROJECTION **See below**

- POWER SUPPLY OPTIONS**
- > **25147** UK mains adaptor
 - > **25428** Euro mains adaptor
 - > **25240** Hardwire transformer
 - > **25241** Battery pack