



## DS112

# DOLPHIN WALL PLATE MOUNTED INFRARED TAP

- › Manufactured from high-quality, highly durable 1.4401 (316) Marine grade stainless steel.
- › Self-monitoring analysis and recording technology (smart) allows the Facilities Manager to connect point to point via the Dolphin InForm App when used with the optional Bluetooth Adaptor (Sold separately – Order product code 25148 )
- › Infrared Touch Free Tap – for ultimate hygiene – prevents cross contamination - sensor mounted in end of 90° spout
- › Designed to be front mounted for when rear access installation is not possible
- › Flow rate: Nominal 3.5 litres/minute as standard (4.0, 1.0, 1.75, 2.0 litres/minute available) at any pressure between 0.5 and 6.0 bar
- › Water supply: single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- › Maximum operating water temperature - 60°C
- › Nominal current: > 1mA (>25mA with Bluetooth). Nominal power: > 1W
- › Security time can be adjusted via the App – default 20 seconds (60 seconds max)
- › IP68 connector
- › Power Source: Plug-in 9 Volt transformer, hard wired transformer, battery pack
- › Recommended minimum distance between sensor and the bottom of basin = 200mm\*\*
- › WRAS approved
- › Comes with Laminar flow to avoid splashing water across the washroom
- › Offset Adaptor fitting available for back-to-back installation
- › Comes as standard with 24 hour line purge/hygiene flush feature, with alterable timings

**DIAMETER** 22MM  
**PROJECTION** 150/175/200/225MM

### PRODUCT CODES

**DS111.xxx.xx xxx** - Main tap code e.g. DS113  
**xxxxx.225.xx xxx** - Tap length, e.g. 225mm  
**xxxxx.xxx.01 xxx** - Tap finish, e.g. 01 = satin  
**xxxxx.xxx.xx BATT** - Power type, e.g. BATT = battery pack





DOLPHIN  
BLUE

