



## DS114

# DOLPHIN WALL PLATE MOUNTED INFRARED TAP

- > Manufactured from high-quality, highly durable 1.4401 (316) Marine grade stainless steel.
- > Self-monitoring analysis and recording technology (smart) allows the facilities Manager to connect point to point via the Dolphin InForm App when used with the optional Bluetooth Adaptor (Sold separately – Order product code 25148 )
- > Infrared Touch Free Tap – for ultimate hygiene – prevents cross contamination - sensor mounted in end of 55° Spout
- > Designed to be front mounted for when rear access installation is not possible
- > Flow rate: Nominal 3.5 litres/minute as standard (4.0, 1.0, 1.75, 2.0 litres/minute available) at any pressure between 0.5 and 6.0 bar
- > Water supply: single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- > Maximum operating water temperature – 60°C
- > Nominal current: > 1mA (>25mA with Bluetooth). Nominal power: > 1W
- > Security time can be adjusted via the App – default 20 seconds (60 seconds max)
- > IP68 connector
- > Power Source: Plug-in 9 Volt transformers
- > Recommended minimum distance between sensor and the bottom of basin = 200mm\*
- > WRAS approved
- > Comes with Laminar flow feature to stop splashing
- > Offset Adaptor fitting available for back-to-back installation
- > Comes as standard with 24 hour line purge/hygiene flush feature, with alterable timings

**DIAMETER** 22MM  
**PROJECTION** 150/175/200/225MM

### PRODUCT CODES

**DS111.xxx.xx xxx** - Main tap code e.g. DS113  
**xxxxx.225.xx xxx** - Tap length, e.g. 225mm  
**xxxxx.xxx.01 xxx** - Tap finish, e.g. 01 = satin  
**xxxxx.xxx.xx BATT** - Power type, e.g. BATT = battery pack





DOLPHIN  
BLUE

