



**Certificate number: 2106701**

Date issued 2nd June 2021

Date expired 1st June 2026 Original/Amendment *Original*

## Kiwa UK Regulation 4 (KUKreg4) Approval

ATS3 – Without Production Surveillance

Issued by Kiwa Watertec (UK)

Evaluation Guideline: Kiwa UK – EG004  
Reference Standards: Regulators Specification  
Model Designations: see Appendix

**Manufacturer: Dolphin Solutions Limited.**

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied on to comply with the above Evaluation Guideline and Standards, and can be marked with the KUKreg4mark.

The intended use of this certificate is for compliance with Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales; 2009 Northern Ireland and 2014 Byelaws Scotland

This certificate has been issued in accordance with the Kiwa regulations for product certification

Signed on behalf of Kiwa Watertec

David Jay,  
Business Unit Manager – Authorised Signatory  
Kiwa Watertec

3901770301

CERTIFICATE

**Kiwa Watertec**  
(A Trading Division of Kiwa Ltd)  
26A Rassau Industrial Estate  
Ebbw Vale  
Gwent  
NP23 5SD  
United Kingdom  
T +44 (0)1495 308185  
[uk.water@kiwa.com](mailto:uk.water@kiwa.com)  
[www.kiwa.co.uk](http://www.kiwa.co.uk)

**Certificate issued to:**  
Dolphin Solutions Limited  
Southpoint, Compass Park  
Bodiam  
East Sussex  
TN32 5BS



# UK Approval Certificate (page 2 of 2)

## Appendix to Certificate 2106701

The following products are covered by this certificate -

<p><b>PRODUCT DESCRIPTION</b>  Range of wall mounted infrared sensor taps with a brass body (various finishes, see model) flow is controlled via solenoid valve. The outlet incorporates an aerator.  ATS3 – Without Production Surveillance.</p>
<p><b>MODEL(S)</b>  Product code – Dsaaa.bbb.c.dd.ee – DS120 Series InForm SMART taps  Where 'aaa' denotes the following options:  DS121 – thru panel mounted;  DS122 – wall plate mounted.  'bbb' denotes spout protection in mm in the range of 100mm to 275mm in 25mm increments.  'c' denotes finish and can be replaced by:  1 – brushed satin, 2- mirror polished, 3 – PVD on brushed/satin, 4 PVD on mirrored polished, 5 – powder coated (PC).  'ee' is a numerical code between 00-99 which denotes the colour of the finished surface and is only applicable on PVD (where 'd' is 3 or 4) or PC (where 'd' is 5)  Some models may include an 'R' suffix which denotes that a rosette is not supplied.</p>
<p><b>SIZE:</b>  ½" BSP(M).</p>
<p><b>SCOPE:</b>  Manufacturer recommended maximum working pressure 6 Bar &amp; maximum operating temperature 60°C.  Hygienic Purposes: Non-metallic materials suitable for continuous use up to 60°C.  Wall Mounted.</p>
<p><b>MATERIALS</b>  Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p><b>BACKFLOW PROTECTION NOTES</b>  Consideration must be made on installation to the airgap arrangement.</p>
<p><b>MARKING</b>  Dolphin logo on body.</p>
<p><b>ADDITIONAL NOTES</b>  All water contact &amp; exposed components satisfy opacity requirements.</p>

### Extra Notes