



## DSI21

# DOLPHIN INFORM STRAIGHT WALL TAP

- > Dolphin Thru Panel Mounted Inform Straight Body Tap
- > Manufactured from high-quality, highly durable 1.4401 (316) Marine grade stainless steel
- > Self-monitoring analysis and recording technology (smart) allows the Facilities Manager to connect point to point via the Dolphin Inform App when used with the optional Bluetooth Adaptor (Sold separately – Order product code 25148 )
- > Infrared Touch Free Tap – for ultimate hygiene – prevents cross contamination – sensor mounted in end of spout
- > Designed to be mounted through an IPS panel\*
- > Flow rate – 3.5 litres/minute (1.25 and 1.75 litres/minute available) with the standard fitted flow regulator (fitted adjacent to solenoid) at any pressure between 0.5 and 6.0 bar
- > 1.0 - 4.0 litres/minute flow rates available to special order – please enquire
- > KUKreg4 compliant
- > Water supply: single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- > Maximum operating water temperature - 60°C
- > Nominal current: Less than 1mA (Less than 25mA with Bluetooth)
- > Nominal power: Less than 1W
- > Security time can be adjusted via the App – default 20 seconds (60 seconds max)
- > IP68 connector
- > Power Source: Plug-in 9 Volt transformers or battery powered
- > Recommended minimum distance between sensor and the bottom of basin = 200mm\*\*
- > Manufactured in the UK
- > Available with a laminar flow option instead of standard aerator

**PROJECTION 100/125/150/175/200/225/250/275MM**  
**DIAMETER 28MM**

