



DS122

DOLPHIN INFORM STRAIGHT WALL TAP – WALL PLATE KIT

- › Dolphin Wall Plate Mounted InForm Straight Body Tap
- › Manufactured from high-quality, highly durable 1.4401 (316) Marine grade stainless steel.
- › Self-monitoring analysis and recording technology (smart) allows the Facilities Manager to connect point to point via the Dolphin InForm App when used with the optional Bluetooth Adaptor (Sold separately -Order product code 25148)
- › Infrared Touch Free Tap – for ultimate hygiene – prevents cross contamination - sensor mounted in end of spout
- › Designed to be front mounted for when rear access installation is not possible
- › Max nominal flow rate of 3.5LPM (between 1 and 6 bar) as standard, and is also available with 1.25LPM and 1.75LPM flow rates on special request
- › KUKreg4 Compliant
- › Manufactured in the UK
- › 1.0 - 4.0 litres/minute flow rates available to special order – please enquire
- › Water supply: single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- › Maximum operating water temperature - 60°C
- › Nominal current: Less than 1mA (Less than 25mA with Bluetooth)
- › Nominal power: Less than 1W
- › Security time can be adjusted via the App – default 20 seconds (60 seconds max)
- › IP68 connector
- › Power Source: Plug-in 9 Volt transformers
- › Recommended minimum distance between sensor and the bottom of basin = 200mm
- › Available with a laminar flow option instead of standard aerator
- › Offset Adaptor fitting available for back-to-back tap installation

PROJECTION 100/125/150/175/200/225/250/275MM
DIAMETER 28MM

