



Certificate number: 2106720

Date issued 8th June 2021

Date expired 7th June 2026 Original/Amendment *Original*

Kiwa UK Regulation 4 (KUKreg4) Approval

ATS3 – Without Production Surveillance

Issued by Kiwa Watertec (UK)

Evaluation Guideline: Kiwa UK – EG004
Reference Standards: Regulators Specification
Model Designations: see Appendix

Factor: Dolphin Solutions Limited.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied on to comply with the above Evaluation Guideline and Standards, and can be marked with the KUKreg4mark.

The intended use of this certificate is for compliance with Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales; 2009 Northern Ireland and 2014 Byelaws Scotland

This certificate has been issued in accordance with the Kiwa regulations for product certification

Signed on behalf of Kiwa Watertec

David Jay,
Business Unit Manager – Authorised Signatory
Kiwa Watertec

CERTIFICATE

3901770301

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate issued to:
Dolphin Solutions Ltd
Southpoint, Compass Park
Bodiam
East Sussex
TN32 5BS



UK Approval Certificate (page 2 of 2)

Appendix to Certificate 2106720

The following products are covered by this certificate -

<p>PRODUCT DESCRIPTION Dolphin Blue range of handheld shower outlets with a stainless body, EPDM o rings (in various finishes) a single check is fitted at the inlet suitable for fluid category 2. Open outlet use only. ATS3 – Without Production Surveillance.</p>
<p>MODEL(S) DB3020.x(.xx): The suffix .x in the above codes – DB3020.x(.xx) - will be a number .1 - .5 to denote the finish: .1 to denote brushed/satin polished, .2 to denote mirror polished, .3 to denote brushed/satin polished with PVD coating, .4 to denote mirror polished with PVD coating & .5 to denote powder coated. .6 - .9 to denote other material and finish options that may be available in the future. The suffix (.xx), in above codes, which when in use appear without the brackets, are only applicable where the previous suffix .3 to .5 are used and they will consist of numbers 00-99 to denote the colour of PVD or powder coat. So for example DB3020.3.50 is brushed/satin polished with Gold PVD coating.</p>
<p>SIZE: ½" BSP(M).</p>
<p>SCOPE: Manufacturer recommended maximum working pressure: Open outlet use only & maximum operating temperature 85°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C. Above ground use only.</p>
<p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p>BACKFLOW PROTECTION NOTES Consideration must be made on installation to the airgap arrangement.</p>
<p>MARKING Dolphin logo on body.</p>
<p>ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.</p>

Extra Notes