



## DB5521.P

# DOLPHIN BLUE 126MM PNEUMATIC CISTERN - 820MM FRAME

- › Concealed WC cistern and frame
- › EN14055 Class two compliant
- › WRAS approved inlet valve
- › Incorporates AUK1 Backflow arrangement
- › Compliant with DEFRA Interim agreement when used with our DC1300 and DC2005 toilet pans
- › In painted profile corrosion resistant
- › Easy and quick installation with Fast Fit system
- › Minimum thickness of 150mm and adjustable up to 170mm
- › Height regulation of the adjustable floor brackets (0-200 mm);
- › Depth adjustable outlet bend
- › Tested for 400kg load
- › Dual flush in-wall cistern compatible with dual flush actuators 6/3 litres (adjustable to 4.5/3 or 4/2.6)
- › 126mm thickness
- › Pneumatic actuation
- › Equipped with delayed refilling Inlet Valve, (can save 9 litres of water per day) and according to BS1212 4:2016
- › Working pressure from 0.1 to 16 bar
- › Resistance to atmospheric humidity (Hr <90%).
- › Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- › Supplied with anti-condensation lining
- › Pre-assembled structure for installation in front of masonry wall and finish in light wall, plasterboard wall and technical support rail for light wall
- › The Dolphin Delayed Action Inlet Valve only opens and starts to refill the cistern once the flush is complete and the flush valve is closed, saving up to 0.5 litres of water per flush

NOTE: Only compliant with the DEFRA interim agreement when used with the specified Dolphin toilet pans

## PRODUCT CODES

- DB5521.E** - Electronic cistern with 820mm frame
- DB5520.E** - Electronic low height cistern without frame
- DB5511.E** - Electronic cistern with 1150mm frame
- DB5510.E** - Electronic cistern without frame
- DB5521.P** - Pneumatic cistern with 820mm frame
- DB5520.P** - Pneumatic low height cistern without frame
- DB5511.P** - Pneumatic cistern with 1150mm frame
- DB5510.P** - Pneumatic cistern without frame